

100-200W

CDA/CNW Series

AC/DC

Features

- Wide range of input voltage
- Broadband noise filter of input
- Surge suppress circuit of input
- Comply with UL1950, IEC950 safety regulation
- Attractive outline design
- Terminal connection method
- Easy installation
- Fast dynamic response



Input Characteristic

Voltage Range 220 VAC 176-264 VAC

Reverse Protection Connect Fuse Outside

Output Characteristic

Voltage Set-point Accuracy	$\pm 1\%$
Line Regulation	$\pm 0.2\%$
Load Regulation	$\pm 0.4\%$
Temperature Coefficient	$\pm 0.01\%/^{\circ}\text{C}$
Output Current Limiting	120%(Typ)
Dynamic Response	400 μs
Output Current	4-20A
Output Voltage	1.8-48V
Power	100-200W

General Characteristic

Switching Frequency	160-200	KHz
Isolation Resistance	200	M Ω
MTBF	>500000	h
Isolation Voltage		
Input-Output	>1500 VAC/1min(Leak <5mA)	
Input-Case	>1500 VAC/1min(Leak <5mA)	
Output-Case	>500 VDC/1min	

Environmental Characteristics

Case Temperature	(Industry) -25 - +85 $^{\circ}\text{C}$
	(Military I) -40 - +85 $^{\circ}\text{C}$
	(Military II) -55 - +85 $^{\circ}\text{C}$
Storage Temperature	(Industry) -45 - +105 $^{\circ}\text{C}$
	(Military) -55 - +105 $^{\circ}\text{C}$

Heat Characteristic

Cooling	Thermal Resistance
Breeze of Nature	2.20 $^{\circ}\text{C}/\text{W}$
0.5M/S	1.84 $^{\circ}\text{C}/\text{W}$
1M/S	1.37 $^{\circ}\text{C}/\text{W}$
1.5M/S	0.99 $^{\circ}\text{C}/\text{W}$
2M/S	0.83 $^{\circ}\text{C}/\text{W}$

CDA/CNW Series 100-200W

AC/DC

Models

Input voltage (Vdc)	Input Range	Output voltage (Vdc)	Output current (A)	Ripple and noise pk-pk(mv)	Efficiency Typical	Models
220	176-264	5	20	50	73%	CDA100W220S05
220	176-264	12	10.4	120	75%	CDA125W220S12
220	176-264	15	8.33	150	75%	CDA125W220S15
220	176-264	24	6.25	200	73%	CDA150W220S24
220	176-264	28	5.36	280	76%	CDA150W220S28
220	176-264	48	4.17	400	76%	CDA200W220S48

Only typical models listed. If you need other model, please contact us for costum models

Mechanical drawing and pin definition

