

105°C Output Capacitor

Soft-start, reduce in-rush impact

Short-circuit / over load protection

**Meet EN60950, EN55015, EN61547
EN61000-3-2, EN6100-3-3, RoHS 5/6
EN61347-1 EN61347-2-13**



Input Characteristic

Input Voltage Range

DC12V±15%
DC15V±15%
DC18V±15%
DC24V±15%
DC36V±15%
DC48V±15%
DC64V±15%
DC100V±15%
DC150V±15%
DC310V±15%
AC110V±15%
AC220V±15%

Input Reverse Protection: No

Input Under Voltage Protection: Yes

Soft Start: Yes

Output Characteristic

Rated	Trim	Eff. %	Max Pow.
24V	22-25V	90±2%	300W
36V	34-37V	90±2%	300W
48V	46-49V	90±2%	300W
64V	62-65V	90±2%	300W
100V	96-103V	90±2%	300W
300V	280-319V	90±2%	300W

Cutstomize input/output pairs are available

Other info

Typical Efficiency:	90±2%
Ripple p-p:	200-300mV
Load Regulation:	±1%~±1.5%
Line Regulation :	±1%~±1.5%
Dynamic response:	±5.0/501us%
SC Protection:	105-130% of Max Pow.
Start Time Delay:	1-2S
Temperature co-efficiency	±0.03%°C(0~50°C)
Non-load consumption:	<2W
Operating temperature:	-30°C ~ +65°C
Operating Humidity:	20%~90%RH
Storage Temperature:	-40°C ~ +85°C
Operating Humidity:	20%~95%RH

Insulation:

Input-Output Input-Case Output-Case:

500VDC/100M Ohms

Isolation:

Input – Output	1.5KVAC
Input – Case	1.5KVAC
Output – Case	0.5KVAC

MTBF:	100000Hrs
Case Material:	aluminium alloy

Built-in Fan:	YES
---------------	-----

Size:	216x115x49 mm
-------	---------------